

EPSON®
EXCEED YOUR VISION



Epson
Stylus Pro 7880



The highest quality A1/24" colour and black & white production printer

Take larger format printing to new levels of quality, stability and consistency. Discover Epson UltraChrome™ K3 ink with Vivid Magenta technology, and combine superb results with improved productivity.

Produce superb neutral black & white images and truly outstanding colour reproduction from one printer. Set new standards with Epson UltraChrome K3 ink with Vivid Magenta technology, three blacks and enhanced image processing technology.

This printer creates results that satisfy the exacting demands of the proofing, photography and fine art markets. It enhances productivity with new printer drivers, simple operation and a wide media choice.

Ideal for proofing, photography and fine art – get contract quality results for demanding applications

Outstanding colour and black & white prints – achieve superb image quality, high colour stability and maximum tonal gradation

A step up in smooth, natural colour – thanks to Epson UltraChrome K3 inks with Vivid Magenta technology

Enhanced image processing technology – extended colour representation of reds and blues

Photo realistic quality that lasts – impressive lightfastness for consistent, repeatable quality

Versatile media handling – choose from an extensive range of matte, gloss and fine art finishes

Improved productivity – fast print speeds and high capacity ink cartridges for overnight printing

Simple operation – customise, share and memorise settings with new printer drivers

Key benefits:

- Setting a new standard in A1/24" production printing
- Epson UltraChrome K3 ink with Vivid Magenta technology
- The perfect proofing, photography and fine art printer
- High versatility through a wide choice of media

Epson Stylus Pro 7880

Size	24" (A1)	
Print technology	Epson Micro Piezo™ drop-on-demand inkjet technology Epson Variable-sized Droplet Technology and 3.5 pl Epson Ultra Micro Dot™ Print head configuration: 180 nozzles x 8 colours	
Ink System	9 colour pigmented ink (C, VM, Y, LC, VLM, LK, LLK, Photo K, Matte K) with CSIC with 8 slots (one slot for interchangeable Matte K and Photo K) Ink conversion cartridges required for ink change between Matte K and Photo K are delivered with the unit	
Resolution	2880 x 1440 dpi Bi-Directional, Epson Variable-sized Droplet Technology	
Speed	Up to 14.3 m ² / Hr (A1 / Plain paper / Draft mode)	
Driver	Microsoft® Windows 2000, XP, XP 64-bit, Vista, MAC OS®X 10.x.x	
Interfaces	Standard: USB 2.0 (Compatible with 1.1), Ethernet 10 / 100Mb	
Roll dimensions	Core diameter 2" or 3". Max. outside diameter ϕ 150 mm	
Paper handling	Single roll (1 roll < 150 mm / Outside diameter)	
Roll media	Media width 203.2 mm – 610 mm (8" – 24") Minimum media length 279 mm Media thickness 0.08 mm – 0.50 mm	
Cut sheet	Manual insertion feeder for media up to 1.5 mm Media width size A4 / LTR – A1+ / 24" (210 mm – 610 mm) Media thickness 0.08 mm – 1.50 mm	
Print margins		
Roll media	3 modes available; mode 1: 3 mm on all edges (top, sides, bottom); mode 2: 15 mm (top and bottom), 3 mm (sides); mode 3: 15 mm (top, sides, bottom)	
Sheet media	2 modes available; mode 1: 3 mm (top, sides, bottom); mode 2: 3 mm (top and sides) 14 mm (bottom)	
Edge-to-edge / Borderless		
Roll media / Cut sheet	Both edge-to-edge and full bleed for the following media widths: 10", 13", 14", 16", 17", 515 mm, 594 mm, 609.6 mm Top and bottom edges can be automatically cut to any length	
Ink cartridges	110 and 220ml ink capacity, single size packaging Pressurised, Intellidige cartridge system for ink level control even on re-inserted cartridges	
	110 ml	220 ml
Matte black	C13T611800	C13T612800
Photo black	C13T602100	C13T603100
Light black	C13T602700	C13T603700
Light light black	C13T602900	C13T603900
Cyan	C13T602200	C13T603200
Vivid magenta	C13T602300	C13T603300
Yellow	C13T602400	C13T603400
Vivid light magenta	C13T602600	C13T603600
Light cyan	C13T602500	C13T603500
Lightfastness	Up to 75 years for colour prints In excess of 100 years for B&W prints	
General		
Dimensions (WxDxH)	1178 mm x 501 mm x 560 mm 1178 mm x 745 mm x 1180 mm (with Stand)	
Weight	Approx. 48.9 kg without ink and media Stand approx. 10.5 kg	
Noise level	Approx. 50dB	
Power consumption	Printing: 55 W or less Standby: 6 W or less Power off: 1 W or less	
Warranty	1 year on-site repair Optional extension to 3 years	
Options	2 / 3" dual roll feed spindle (High tension) C12C811155 Maintenance tank (x2) C12C890191	



For further information please contact your local Epson office or visit www.epson-europe.com

Austria 0810/20 01 13 (0,07 €/Min.) Belgium 070/350120 (0.1735 €/min.) Czech 800/142 052 Denmark 44 50 85 85
Finland 0201 552 091 France 0892 899 999 (0,34 €/min) Germany 01805/23 41 10 (0,14 €/Min.) Greece 210-8099499
Hungary 06800 147 83 Ireland 1 800 409132 Italy 02-660321 10 (0,12 €/min.) Luxembourg 900/43010 (0,24 €/min.)
Middle East +9714 8818934 Netherlands 0900-5050808 (0.05 €/oproep + 0.15 €/min.) Norway 22 06 42 80
Poland 0-0-800 4911299 (0,16 zTJ/min.) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429
South Africa (+2711) 465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala
samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 0848 448820 (4-8 cent./min.) Turkey (0212) 3360303
United Kingdom 08702 416900

Entity carrying out management and coordination pursuant to article 2497 bis of Civil Code: Epson Europe BV

EPSON® is a registered trademark of Seiko EPSON® Corporation. All other product names and other company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice.

EPSON®